

See our full line of products on our web site:

[www.custom-products.com](http://www.custom-products.com)

**Custom Products & Services, Inc.**

6140 Claude Way E.,

Inver Grove Hts., MN. 55076

PH: 888-444-1202 FAX: 651-452-2264

E-Mail: [info@custom-products.com](mailto:info@custom-products.com)

Website: [www.custom-products.com](http://www.custom-products.com)




25-H CAM



25-C CAM



25-F CAM



25-S CAM



25-R CAM



**FOR A-3 HOUSING**

25-C cam is discontinued.  
Replace with 25-H

**FOR A-4 HOUSING**



**NOTE:**

Some tools require special cams.

> 25-800 for SR-100 Snap Ring Tool

> BC-6 for BC-004 and BC-006 Ball Crimp Tool

**ALL CAMS MUST BE LOCTITED IN PLACE**



25-800 CAM



BC-6 CAM

# Recommended Jaw Selection Chart

JAWS	POWER PACKS								
	SP-01	SP-02	SP-001	SP-002	SP-003	SP-004	SP-006	SP-005	SP-008
<b>CD-1</b>	3/32 (2.36mm) max. copper / alum.	1/8 (3.17mm) max. soft copper / alum.							
<b>CD-3</b>	1/16 (1.57mm) max. soft steel	3/32 (2.36mm) max. soft steel							
<b>CD-4</b>	1/16 (1.57mm) max. med. wire	3/32 (2.36mm) max. med. wire							
<b>CD-5</b>									
<b>CD-6</b>									
<b>FS-1</b>	3/32 (2.36mm) max. soft wire	1/8 (3.17mm) max. soft wire							
<b>PGC-2</b>	1/8 (3.17mm) max. plastic gates	3/16 (4.75mm) max. plastic gates							
<b>C-23</b>			1/8 (3.17mm) max. soft wire	3/16 (4.75mm) max. soft wire					
<b>C-24</b>			1/16 (1.57mm) max. hard wire	3/32 (2.36mm) max. hard wire					
<b>B-31</b>					3/32 (2.36mm) max. mild steel	1/8 (3.17mm) max. mild steel	5/32 (3.96mm) max. mild steel	5/32 (3.96mm) max. mild steel	3/8 (9.53mm) mild steel
<b>B-32</b>					5/32 (3.96mm) max. mild steel	7/32 (5.54mm) max. mild steel	9/32 (7.14mm) max. mild steel	9/32 (7.14mm) max. mild steel	3/8 (9.53mm) mild steel
<b>B-33</b>					5/32 (3.96mm) max. mild steel	7/32 (5.54mm) max. mild steel	9/32 (7.14mm) max. mild steel	9/32 (7.14mm) max. mild steel	3/8 (9.53mm) mild steel
<b>D-31</b>					3/32 (2.36mm) max. mild stl./cop. alum.	1/8 (3.17mm) max. mild stl./cop. alum.	5/32 (3.96mm) max. mild stl./cop. alum.	5/32 (3.96mm) max. mild stl./cop. alum.	1/4 (6.35mm) mild stl./cop. alum.
<b>D-33</b>					1/8 (3.17mm) max. mild stl./cop. alum.	3/16 (4.75mm) max. mild stl./cop. alum.	7/32 (5.54mm) max. mild stl./cop. alum.	7/32 (5.54mm) max. mild stl./cop. alum.	5/16 (7.94mm) mild stl./cop. alum.
<b>D-4</b>					3/32 (2.36mm) max. mild stl./cop. alum.	1/8 (3.17mm) mild stl./cop. alum.	5/32 (3.96mm) mild stl./cop. alum.	5/32 (3.96mm) mild stl./cop. alum.	7/32 (5.55mm) mild stl./cop. alum.
<b>E-3</b>					3/16 (4.76mm) max. elec. cab./software	1/4 (6.35mm) max. elec. cab./software	5/16 (7.94mm) max. elec. cab./software	5/16 (7.94mm) max. elec. cab./software	3/8 (9.53mm) elec. cab./software
<b>E-4</b>					3/32X1/4 (2.36X6.35) elec. cab./software	1/8X5/16 (3.17X7.92) elec. cab./software	3/16X1/2 (4.75X12.7) elec. cab./software	3/8 (9.53mm) elec. cab./software	1/2 (12.70mm) elec. cab./software
<b>PGC-4</b>					3/16 (4.75mm) max. plastic gates	1/4 (6.35mm) max. plastic gates	3/8 (9.53mm) max. plastic gates	3/8 (9.53mm) max. plastic gates	1/2 (12.70mm) max. plastic gates