
ALIGN® WORKBENCHES: ERGONOMIC. CUSTOMIZABLE. MULTI-USER FRIENDLY.

Versatile Align workstations are ideally suited for environments where multiple users utilize the same workspace. Designed with the operator in mind, they easily adjust in height to align to individual user comfort and changing tasks. This "comfort customization" helps reduce fatigue, stress, and injury potential and increase productivity by providing each user with tailored ergonomic support and flexible functionality.





E-MAIL: Info@custom-products.com Website: www.custom-products.com "YOUR SOURCE FOR WORKPLACE SOLUTIONS"











ALIGN® ADJUSTABLE HEIGHT WORKSTATIONS

Model ALE/R workstations include an Align rear-justified motorized base. Model ALC/R workstations include an Align rear-justified crank base.

See page 45 for hanging cabinet descriptions.

How to order an Easy-Order **Align Adjustable Height Workstation**

1. Select Easy-Order workstation configuration.

2. Select worksurface style. See page 42 for worksurface descriptions.

PLB = Plastic laminate BTB = Butcher block SDB = Static dissipative

(includes ground cord and hardware)

All worksurfaces have a bullnose front edge and are 30" deep.

3. Select worksurface size.

6030 = 60" long x 30" deep 7230 = 72" long x 30" deep

4. Select paint color. Add 2-letter paint code shown in color chart on inside back cover.

5. Select lock type for models with hanging cabinet.

RG = individual KA = keyed-alike MA = master KP = Keypad

EXAMPLE: to order an ALE/R5201 workstation with a 72" long plastic laminate worksurface and shelf and Classic Blue paint, with an individual lock for the hanging cabinet, the part number would be ALE/R5201-PLB7230CB, with a WBHC450-2-RG hanging cabinet.





ALC/R5100-



ALE/R5001-

ALC/R5001-

DESCRIPTION

motorized

hand crank

P.

Α A




ART NO.	DESCRIPTION
ALE/R5002-	motorized
ALC/R5002-	hand crank




WBHC150-1-

hanging cabinet




ALE/R5101-	WBHC150-1	
	hanging cabinet	
ALC/R5101-	WBHC150-1-	
	hanging cabinet	



FARTINO.	INCLUDES	
ALE/R5102-	WBHC150-1-	
	hanging cabinet	
ALC/R5102-	WBHC150-1-	
	hanging cabinet	





Workstations with

Workstations with **Instrument Riser Shelf** Includes:

- (2) 16" instrument riser supports (1 with power)
- 12" deep instrument riser shelf
- Worksurface and shelf back stops

ALIGN WORKBENCH WORKSURFACES

Lista worksurfaces are all easy to maintain, rugged, and durable.

Worksurfaces come in 30", 60", 72", and 90" lengths, and are 24", 30", 36" or 48" deep, depending on worksurface. Other sizes are available, and certain worksurfaces are available with a bullnose front edge.

Butcher Block Worksurface-Sq Edge (BB), Bullnose (BN)

- Satin finish 1 ¾" thick hardwood
- Available in standard square edge or bullnose front edge



Lista Top (LT)


 1 ¾" thick worksurface with wood core and 3/8" sanded, oil resistant pressed wood, top and bottom



Static Dissipative Plastic Laminate

Particle board core with plastic laminated top and sides, 1 ⁹/16" thick. Grounding bolt and 10' grounding cord with a 1 megohm resistor included (installation required). Standard color is dove gray but other colors available on request. Available in standard square edge or bullnose front edge (shown above). To order a bullnose edge, add "BN" to end of part number.

Worksurfaces display electrical properties within static dissipative boundaries of 10⁶-10⁹ ohms over a wide range of relative humidities (ranging from 60% RH to as low as 10% RH) to meet ESD specifications. Meets EOS/ESD S4.1 specifications. For detailed specifications, please contact Lista.



PART NO.	LENGTH
36″ deep	
SDTOP-3036	30″
SDTOP-4836	48″
SDTOP-6036	60″
SDTOP-7236	72″
SDTOP-9036	90″
48" deep	
SDTOP-60X48	60″
SDTOP-72X48	72″
SDTOP-90X48	90″



Butcher Block

PART NO.	LENGTH
24" deep	
BTOP-3024	30″
BTOP-4824	48″
BTOP-6024	60″
BTOP-7224	72″
BTOP-9024	90″

30" deep BTOP-30 30" BTOP-48 48" BTOP-60 60" BTOP-72 72" BTOP-90 90"

36" deep

BTOP-3036	30"	
BTOP-4836	48″	
BTOP-6036	60″	
BTOP-7236	72″	
BTOP-9036	90″	

48" deep

to accp		
BTOP-60X48	60″	
BTOP-72X48	72″	
BTOP-90X48	90″	

Lista Top (LT)

PART NO.	LENGTH	
30" deep		
LTOP-30	30″	
LTOP-48	48″	
LTOP-60	60″	
LTOP-72	72″	
LTOP-90*	90″	

36″ deep

LTOP-3036	30″	
LTOP-4836	48″	
LTOP-6036	60″	
LTOP-7236	72″	
LTOP-9036	90″	

Static Dissipative Plastic Laminate PART NO. LENGTH

24" deep		
SDTOP-3024	30″	
SDTOP-4824	48″	
SDTOP-6024	60″	
SDTOP-7224	72″	
SDTOP-9024	90″	

30" deep

30" deep		
SDTOP-30	30″	
SDTOP-48	48″	
SDTOP-60	60″	
SDTOP-72	72″	
SDTOP-90	90″	



ALIGN WORKBENCH WORKSURFACES

Galvanized Steel Over Wood

Lista Top with additional heavy-gauge galvanized steel cover that is fitted over top and sides of Lista Top, 1 ¹³/₆" thick.



Stainless Steel Over Wood

Worksurface is constructed of durable, heavy gauge stainless steel, fitted over top and sides of partial board, 1¹³/₆" thick.



Plastic Laminate

Particle board core with plastic laminated top and sides. 1 %⁶" thick. Dove gray is standard but other colors are available on request. Available in standard square edge or bullnose front edge. To order a bullnose edge, add "BN" to the end of the part number.



Galvanized Steel Over Wood PART NO. LENGTH

30" deep		
LSTOP-30	30"	
LSTOP-48	48″	
LSTOP-60	60″	
LSTOP-72	72″	
LSTOP-90	90″	

36″ deep

so accp		
LSTOP-3036	30″	
LSTOP-4836	48″	
LSTOP-6036	60″	
LSTOP-7236	72″	
LSTOP-9036	90″	

Stainless Steel Over Wood PART NO. LENGTH

30" deep		
LSSTOP-30	30"	
LSSTOP-48	48″	
LSSTOP-60	60″	
LSSTOP-72	72″	
LSSTOP-90	90″	

36" deep

30 ueep	
LSSTOP-30X36	30″
LSSTOP-48X36	48″
LSSTOP-60X36	60″
LSSTOP-72X36	72″
LSSTOP-90X36	90″

Plastic Laminate PART NO. LENGTH

24" deep		
PTOP-3024	30″	
PTOP-4824	48″	
PTOP-6024	60″	
PTOP-7224	72″	
PTOP-9024	90″	

30" deep

PTOP-30	30″
PTOP-48	48″
PTOP-60	60″
PTOP-72	72″
PTOP-90	90″

36" deep

PTOP-3036	30"	
PTOP-4836	48″	
PTOP-6036	60″	
PTOP-7236	72″	
PTOP-9036	90″	

48" deep

ie acep		
PTOP-60X48	60″	
PTOP-72X48	72″	
PTOP-90X48	90″	



ALIGN[®] ADJUSTABLE HEIGHT WORKSTATION OPERATOR-**ADJUSTABLE BASES**

Motorized Bases

- · Features a low-EMS, low-voltage dual actuator controller for synchronized leg movement and stress-free operation
- Three height positions can be preset with the programmable switch
- Static and dynamic load capacity is 1,000 lbs.
- Height range (floor to top of base, not including worksurface) is 27"-42"
- Worksurface not included see page 42 for worksurface choices
- Some assembly required



Motorized Bases, Rear-Justified

PART NO.	BASE WIDTH	WORKSURFACE LENGTH (MIN.)
24" deep		
ALE/R3024	29″	30"
ALE/R4824	47″	48″
ALE/R6024	59″	60"
ALE/R7224	71″	72″
ALE/R9024	89″	90″
30" deep		
ALE/R3030	29″	30"
ALE/R4830	47″	48″
ALE/R6030	59″	60″
ALE/R7230	71″	72″
ALE/R9030	89″	90″
36" deep		

36" deep		
ALE/R3036	29″	30"
ALE/R4836	47″	48″
ALE/R6036	59″	60"
ALE/R7236	71″	72″
ALE/R9036	89″	90″

Motorized Bases, Center-Justified

PART NO.	BASE	WORKSURFACE LENGTH (MIN.)
30" deep	WIDTH	LEINGTH (MIIN.)
ALE/C3030	29″	30″
ALE/C4830	47″	48″
ALE/C6030	59″	60″
ALE/C7230	71″	72″
ALE/C9030	89″	90″
36" deep		
ALE/C3036	29″	30″
ALE/C4836	47″	48″
ALE/C6036	59″	60″
ALE/C7236	71″	72″
ALE/C9036	89″	90″
48" deep		
ALE/C6048	59″	60″
ALE/C7248	71″	72″

ALE/C6048	59″	60″	
ALE/C7248	71″	72″	
ALE/C9048	89″	90″	

Hand Crank Bases

- Hand crank static load capacity is 1,000 lbs., dynamic load capacity is 500 lbs.
- Height range (floor to top of base, not including worksurface) is 27"-42"
- Worksurface not included see page 42 for worksurface choices
- Some assembly required



Hand Crank Bases, Rear-Justified

PART NO.	BASE WIDTH	WORKSURFACE LENGTH (MIN.)
24" deep		
ALC/R3024	29″	30″
ALC/R4824	47″	48″
ALC/R6024	59″	60″
ALC/R7224	71″	72″
ALC/R9024	89″	90″
30" deep		
ALC/R3030	29″	30"
ALC/R4830	47″	48″
ALC/R6030	59″	60″
ALC/R7230	71″	72″
ALC/R9030	89″	90″
36" deep		
ALC/R3036	29″	30″
ALC/R4836	47″	48″
ALC/R6036	59″	60″
ALC/R7236	71″	72″
ALC/R9036	89″	90″

Hand Crank Bases, Center-Justified

PART NO.	BASE WIDTH	WORKSURFACE LENGTH (MIN.)
30" deep		
ALC/C3030	29″	30″
ALC/C4830	47″	48″
ALC/C6030	59"	60″
ALC/C7230	71″	72″
ALC/C9030	89″	90″
36" deep		
ALC/C3036	29″	30″
ALC/C4836	47″	48″
ALC/C6036	59"	60″
ALC/C7236	71″	72″
ALC/C9036	89″	90″
48" deep		
ALC/C6048	59"	60″
ALC/C7248	71″	72″
ALC/C9048	89″	90″



DESCRIPTION

Casters

PART NO.

ALIGN® ADJUSTABLE HEIGHT WORKSTATION ACCESSORIES

Casters

- Casters can be added to any adjustable height base to allow mobility
- Caster is 5" diameter, increases overall height 6". 325 lb. capacity per caster

Offset Caster Assembly

- Offset caster assemblies do not increase the overall height range of the base
- Welded frame replaces standard feet • Includes pair of offset frames with
- (2) 5" swivel casters and (2) 5" swivel-with-wheel-lock casters
- Rear casters extend 4" beyond back of worksurface
- Painted to match base
- For motorized and hand crank bases only

Workstation Hanging Cabinets


- 16 ¾" (426mm) wide x 19 ¼" (491mm) deep
- Cabinet is suspended from the worksurface
- 50 lb. (22.5kg) weight capacity per drawer
- Usable inside dimensions: 13 1/4" (338.5mm) wide x 16 15/16" (430mm) deep
- Drawers do not accept Lista partitions and dividers
- Not available for center-justified or 24" deep rear-justified Align workstations. Cabinet can not be positioned at same end of bench as keypad or hand crank.
- Comes with individual lock and 2 keys

How to order a hanging cabinet 1. Select cabinet.

- 2. Select lock type.*
- NL = none
- KA = keyed-alike
- RG = individual
- MA = master
- **KP** = keypad

3. Select paint color. For color chart, see inside back cover.

*units ordered without lock can not have lock installed at a later date



FOR USE WITH THESE BENCHES

2

3

Δ

6

7

8

9

10

11 12

ALIGN[®] ADJUSTABLE HEIGHT WORKSTATION ACCESSORIES

Align Bottom Shelves

- Provides open storage beneath worksurface
- 16" deep
- Accepts vertical wire dividers (see below)
- 150 lb. (68kg) capacity
- For motorized and hand crank bases only

Vertical Wire Dividers for Bottom Shelves

- 15" deep dividers are ¹/4" diameter galvanized wire that fit into pre-punched holes in the 16" deep shelf
- No hardware required

CPU Holder

- Mounts to underside of worksurface
- 9 ¹/2" wide x 18" deep x 20" high
- Painted to match workstation

Adjustable CPU Holder

- Adjustable pullout CPU holder has 360° rotation
- Accommodates CPU width range of 2"-8 ½" and CPU height range of 11"-22"
- Mounts to worksurface support beams

Keyboard Holder


- Tiltable keyboard holder allows computer keyboard to be stored under worksurface when not in use
- Includes swivel pull-out mouse pad which can be attached to either right or left side

Align Attached Footrest

- Ergonomic footrest attaches over Align base stringer
- Height adjustable from 3"-12 ¹/4" (plus height of stringer)
- Footrest platform is 15" deep x 21 ³/₄" wide, and adjusts from totally flat to a 25° angle
- Ribbed mat included
- Not compatible with 30" wide Align workstations

Freestanding Footrest

- Ergonomic footrest provides support for user's feet
- Height adjustable from 3"-12 1/4"
- Footrest platform is 15" deep x 21 $\frac{3}{4}$ " wide, and adjusts from totally flat to a 25° angle
- Ribbed mat included













Bottom Shelves PART NO. LENGTH ALBS/F-4816 48" ALBS/F-6016 60" ALBS/F-7216 72"

90'

ALBS/F-9016

Wire Dividers PART NO.	HEIGHT
NXS/WD150-15	6″
NXS/WD250-15	10″
NXS/WD450-15	18″

CPU Holder PART NO. CPU/H

Adjustable CPU Holder PART NO. CPU/H-ADJ/SOR

Keyboard Holder	
WB/KBH	21" x 10"

Attached Footrest PART NO. AL/AFR

Freestanding Footrest WB/FFR



ALIGN[®] ADJUSTABLE HEIGHT WORKSTATION ACCESSORIES

Nexus Rear-Mount Frames

- For use with Align® rear-justified adjustable height bases only
- Starter frames consist of 2 upright posts, a horizontal rail, brackets and hardware
- Adder sets consist of an additional upright, a horizontal rail and a bracket
- Frames are sturdy, heavy gauge steel, and are notched front and back at 1" increments for mounting accessories
- Uprights are available in heights of 30" and 48" (height = usable height above top of base), and widths of 24", 30", 36", 42", 48" and 60"
- Specify color from chart on the inside back cover
- Must be inset 3" to center of upright. For wider applications see Nexus Extender Rear mount frames below



30" High* Rear-Mount Frames

PART NO. Starter set	SEC. WIDTH CENTTO-CENT.
NXF/RM2430	24"
NXF/RM3030	30″
NXF/RM3630	36″
NXF/RM4230	42"
NXF/RM4830	48"
NXF/RM6030	60"

24″

30″

36″

42″

48″

60″

48" High* Rear-Mount Frames

PART NO. Starter set	SEC. WIDTH CENTTO-CENT.
NXF/RM2448	24"
NXF/RM3048	30"
NXF/RM3648	36"
NXF/RM4248	42″
NXF/RM4848	48"
NXF/RM6048	60"
Adder set	
NXF/RM2448A	24″
NXF/RM3048A	30"
NXF/RM3648A	36"
NXF/RM4248A	42"
NXF/RM4848A	48"
NXF/RM6048A	60"

* upright overall height is 48"

Adder set NXF/RM2430A

NXF/RM3030A

NXF/RM3630A

NXF/RM4230A

NXF/RM4830A

NXF/RM6030A

* upright overall height is 60"

Nexus Extended Rear-Mount Frames

- For use with Align[®] rear-justified adjustable height bases only
- Allows use of the full width of an Align rear-justified adjustable height workstation for support of a Nexus system
- The total width of the extended rear-mount frame must equal the width of the Align workstation
- Extended rear-mount frame is the starter set; use the standard rear-mount adder for adder unit
- Not for use with Align workstations that are placed flush side-to-side
- Specify color from chart on back cover
- Extends approximately ³/₄" beyond end of work surface at each end



30" High* Extended Rear-Mount Frames

PART NO.	WIDTH	
NXF/RM2430-EXT	24″	
NXF/RM3030-EXT	30″	
NXF/RM3630-EXT	36″	
NXF/RM4230-EXT	42″	
NXF/RM4830-EXT	48″	
NXF/RM6030-EXT	60"	

48" High* Extended Rear-Mount Frames

PART NO.	WIDTH	
NXF/RM2448-EXT	24″	
NXF/RM3048-EXT	30"	
NXF/RM3648-EXT	36″	
NXF/RM4248-EXT	42″	
NXF/RM4848-EXT	48″	
NXF/RM6048-EXT	60″	

* upright overall height is 48"

* upright overall height is 60"