

# Specification Sheet

## Short Form Specifications

Eagle Stem Caster, model \_\_\_\_\_. For use with 1"-diameter posts. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. For electronic handling, conductive casters available. Donut bumper included with all stem casters. Swivel casters have a temperature rating of -15°F (-26°C). Note: These stem casters cannot be used with Master Trak® Shelving.

## Stem Casters

### MODELS:

- |  |  |   |   |
|--|--|---|---|
| <input type="checkbox"/> <b>CSS4-125</b> | <input type="checkbox"/> <b>CSB5P-*</b>  | <input type="checkbox"/> <b>CSPB5-300</b> | <input type="checkbox"/> <b>A201008</b> |
| <input type="checkbox"/> <b>CSS5-*</b>   | <input type="checkbox"/> <b>CSR5P-*</b>  | <input type="checkbox"/> <b>CPSS5PS-*</b> | <input type="checkbox"/> <b>A201009</b> |
| <input type="checkbox"/> <b>CSB5-*</b>   | <input type="checkbox"/> <b>CSS5PS-*</b> | <input type="checkbox"/> <b>CPSB5PS-*</b> | <input type="checkbox"/> <b>A204795</b> |
| <input type="checkbox"/> <b>CSR5-*</b>   | <input type="checkbox"/> <b>CSB5PS-*</b> | <input type="checkbox"/> <b>A201706</b>   | <input type="checkbox"/> <b>A207562</b> |
| <input type="checkbox"/> <b>CSS5P-*</b>  | <input type="checkbox"/> <b>CSR5PS-*</b> | <input type="checkbox"/> <b>A201007</b>   | <input type="checkbox"/> <b>A200019</b> |
|  |  |   | <input type="checkbox"/> <b>A213261</b> |

\* See charts for complete model numbers.



swivel caster with resilient tread



(nickel-plated) caster with polyurethane tread



conductive caster

### Casters with Resilient Tread

type	EAGLEbrite® zinc capacity			stainless steel capacity			wheel diameter		wheel face		weight	
	model #	lbs.	kg	model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CSS4-125</b>	125	56.7	n/a			4"	102	1"	25	1.1	0.5
swivel	<b>CSS5-125</b>	125	56.7	n/a			5"	127	1"	25	2.0	0.9
swivel	<b>CSS5-300</b>	300	136.1	<b>CSS5S-300</b>	300	136.1	5"	127	1 1/4"	32	2.5	1.2
w/brake	<b>CSB5-300</b>	300	136.1	<b>CSB5S-300</b>	300	136.1	5"	127	1 1/4"	32	2.8	1.3
w/step-pedal brake	<b>CSPB5-300</b>	300	136.1	n/a			5"	127	1 1/4"	32	2.8	1.3
rigid ▼	<b>CSR5-300</b>	300	136.1	<b>CSR5S-300</b>	300	136.1	5"	127	1 1/4"	32	3.5	1.6

### Casters with Polyurethane Tread

type	nickel-plated model #	stainless steel capacity		wheel diameter		wheel face		weight		
		model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CSS5P-300</b>	<b>CSS5PS-300</b>	300	136.1	5"	127	1 1/4"	32	2.5	1.1
w/brake	<b>CSB5P-300</b>	<b>CSB5PS-300</b>	300	136.1	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	<b>CSR5P-300</b>	<b>CSR5PS-300</b>	300	136.1	5"	127	1 1/4"	32	3.5	1.6

### Conductive Casters For electronic handling only.

type	EAGLEbrite® zinc capacity		wheel diameter		wheel face		weight		
	model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CSS5-CC</b>	200	90.7	5"	127	1 1/4"	32	2.5	1.1
w/brake	<b>CSB5-CC</b>	200	90.7	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	<b>CSR5-CC</b>	200	90.7	5"	127	1 1/4"	32	3.5	1.6

▼ See back page for optional Channel Frames available for use with rigid casters.

### Certifications / Approvals





## Stem Casters



cart-washable  
caster

### Cart-Washable Casters

Features stainless steel boot, swivel stem, sealed precision bearings, and polyurethane wheel.

type	stainless steel model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CSS5WPS-300</b>	300	136.1	5"	127	1 1/4"	32	2.0	0.9
brake	<b>CSB5WPS-300</b>	300	136.1	5"	127	1 1/4"	32	2.0	0.9




polymer caster

### Polymer Casters

With polyurethane tread.

type	model #	type of bearing	capacity		wheel diameter		wheel face		weight	
			lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CPSS5-250</b>	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9
brake	<b>CPSB5-250</b>	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9



channel frame

### Channel Frames—for Rigid Stem Casters

Please note that shelf width must be known when ordering rigid stem casters in order to ship appropriate channel frame to lock rigid casters.

model #	shelf width		weight	
	in.	mm	lbs.	kg
<b>A201706</b>	14"	356	1.5	0.7
<b>A201007</b>	18"	457	2.0	0.9
<b>A201008</b>	21"	533	2.5	1.1
<b>A201009</b>	24"	610	2.8	1.3
<b>A204795</b>	30"	762	3.5	1.6
<b>A207562</b>	36"	914	4.0	1.8



donut bumper  
#A200019

### Donut Bumpers—for all Stem Casters

description	model #
3 1/2" (89mm) diameter	<b>A200019</b>
5" (127mm) diameter, with swivel center	<b>A213261</b>

# Specification Sheet

## Short Form Specifications

Eagle Plate Caster, model \_\_\_\_\_. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. 5" to 8" wheel diameter.

## Plate Casters

### MODELS:

- |                                  |                                  |                                    |
|----------------------------------|----------------------------------|------------------------------------|
| <input type="checkbox"/> CPS*-*  | <input type="checkbox"/> CPR*P-* | <input type="checkbox"/> PCPS5-250 |
| <input type="checkbox"/> CPB*-*  | <input type="checkbox"/> CPL*Z-* | <input type="checkbox"/> PCPL5-250 |
| <input type="checkbox"/> CPR*-*  | <input type="checkbox"/> CPS*Z-* | <input type="checkbox"/> CPS5S-300 |
| <input type="checkbox"/> CPS*P-* | <input type="checkbox"/> CPR*Z-* | <input type="checkbox"/> CPB5S-300 |
| <input type="checkbox"/> CPB*P-* | <input type="checkbox"/> CPB*Z-* |                                    |

\* See charts for complete model numbers.



resilient plate caster

### Casters with Resilient Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5-200	200	90.7	5"	127	1 1/8"	29	2.8	1.3
brake	CPB5-200	200	90.7	5"	127	1 1/8"	29	2.8	1.3
rigid	CPR5-200	200	90.7	5"	127	1 1/8"	20	2.8	1.3
swivel	CPS5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
rigid	CPR5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
swivel	CPS6-500	500	226.8	6"	152	2"	51	9.0	4.1
brake	CPB6-500	500	226.8	6"	152	2"	51	9.0	4.1
rigid	CPR6-500	500	226.8	6"	152	2"	51	9.0	4.1



polyurethane plate  
caster with brake

### Casters with Polyurethane Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
rigid	CPR5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
swivel	CPS5P-500	500	226.8	5"	127	2"	51	8.0	3.6
brake	CPB5P-500	500	226.8	5"	127	2"	51	8.0	3.6
rigid	CPR5P-500	500	226.8	5"	127	2"	51	8.0	3.6
swivel	CPS6P-600	600	272.1	6"	152	2"	51	9.0	4.1
brake	CPB6P-600	600	272.1	6"	152	2"	51	9.0	4.1
rigid	CPR6P-600	600	272.1	6"	152	2"	51	9.0	4.1
swivel	CPS8P-700	700	317.5	8"	203	2"	51	10.5	4.8
brake	CPB8P-700	700	317.5	8"	203	2"	51	10.5	4.8
rigid	CPR8P-700	700	317.5	8"	203	2"	51	10.5	4.8

### Certifications / Approvals





Profit from the Eagle Advantage®



**CUSTOM PRODUCTS & SERVICES**  
6286 Claude Way E, Inver Grove Heights, MN 55076-4435  
PH: 888-444-1202 (Toll Free) or 651-452-0113 Fax: 651-452-2264

E-mail: [Info@custom-products.com](mailto:Info@custom-products.com)  
Website: [www.custom-products.com](http://www.custom-products.com)

## Plate Casters

### Swivel/Lock Casters

Polyurethane tread.



swivel/lock plate caster

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel/lock	<b>CPL6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
swivel	<b>CPS6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
rigid	<b>CPR6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
brake	<b>CPB6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
swivel/lock	<b>CPL8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8
swivel	<b>CPS8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8
rigid	<b>CPR8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8
brake	<b>CPB8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8



polymer  
plate caster

### Polymer Casters

Polyurethane tread.

type	model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>PCPS5-250</b>	250	90.7	5"	127	1 1/4"	32	2.8	1.3
lock	<b>PCPL5-250</b>	250	90.7	5"	127	1 1/4"	32	2.8	1.3



stainless steel  
pressure-washable  
caster (with brake)

### Stainless Steel Pressure-Washable Casters

Polyurethane tread.

type	model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CPS5S-300</b>	300	136.1	5"	127	1 1/4"	32	3.0	1.4
brake	<b>CPB5S-300</b>	300	136.1	5"	127	1 1/4"	32	3.0	1.4