



CUSTOM PRODUCTS & SERVICES INC.
6286 Claude Way E., Inver Grove Heights Mn, 55076
PH: 888-444-1202 (Toll Free) or 651-452-0113 Fax: 651-452-2264
E-MAIL: Info@custom-products.com
Website: www.custom-products.com
"YOUR SOURCE FOR WORKPLACE SOLUTIONS"

SR-100 UNIVERSAL SNAP RING TOOL – PNEUMATIC



The SR-100 **Internal** Snap Ring Tool is designed to work with snap rings ranging from 1/4" – 6" diameter. A range of tip sizes and angles are available. Tips are ordered separately.

External snap ring tools are available on a custom order basis only.

Tip Spacing Adjustment: To adjust the tip spacing, remove the Allen head screw on the back end of the power pack with a 1/8" Allen Screwdriver. Then, with a 3/32" Allen head screwdriver, remove the small set screw down inside. Now you can access the adjustment screw (3/32") to set the tip spacing. Clockwise to close the jaw tip spacing, or counter-clockwise open the jaw tip spacing. Maximum open spacing is 1.5". Maximum close tip spacing is .125"



Tool Specifications.

Tool Length: 11" (with tips)
Tool Length: 10" (without tips)
Tool Weight: 1.75 lbs.
Tool Diameter: 1.5"

Tip Sizes:

.093, .109" & .120"

Tip Angles:

Straight, 45-deg, 90-deg